

## Intara XR

Article number: 50730030

### LIGHT TECHNOLOGY

|                      |           |
|----------------------|-----------|
| LED                  | COB       |
| Light colour         | BeCool    |
| Luminous flux        | 2750 lm   |
| System power         | 34 W      |
| Luminaire Efficiency | 81 lm/W   |
| Reflector            | OvalBasic |
| Beam angle           | 60° x 40° |
| Controller           | On/Off    |

### LUMINAIRE

|                           |            |
|---------------------------|------------|
| Rotation angle            | 400°       |
| Swivel angle              | +/- 85°    |
| Weight                    | 0.65 kg    |
| Protection rating . class | IP 20 . II |
| Luminaire colour          | white      |

### OPTIONEEL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Semi-recessed luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented, die-cast aluminium, powder-coated, rotation angle 400°, swivel angle +/- 85°, white, separate driver unit

76500076 driver unit, On/Off, 220-240 V / 50-60 Hz, 850 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500077 driver unit, DALI, 220-240 V / 50-60 Hz, 850 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

