

## Intara XR

Article number: 50890007

### LIGHT TECHNOLOGY


LED	COB
Light colour	BeCool
Luminous flux	1280 lm
System power	15 W
Luminaire Efficiency	85 lm/W
Reflector	Flood
Beam angle	40°
Controller	On/Off

### LUMINAIRE

Swivel angle	+/- 25°
Weight	0.69 kg
Protection rating . class	IP 20 . II
Luminaire colour	black

### OPCJA


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Recessed luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, die-cast aluminium, powder-coated, rotation angle, swivel angle +/- 25°, black,

Inclusiv fix connected driver unit, 220-240 V~ / 50-60 Hz, max. 36 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



Distance (m)	Beam Diameter (m)	Illuminance E0(0°) [lx]
1.0 m	0.81	2252.3
2.0 m	1.62	563.1
3.0 m	2.43	250.3
4.0 m	3.24	140.8
5.0 m	4.05	90.1

