

Intara XR

Article number: 50900055

LIGHT TECHNOLOGY



LED	COB
Light colour	BeColor
Luminous flux	2800 lm
System power	34 W
Luminaire Efficiency	82 lm/W
Reflector	OvalBasic
Beam angle	60° x 40°
Controller	On/Off

LUMINAIRE

Swivel angle	+/- 25°
Weight	0.69 kg
Protection rating . class	IP 20 . II
Luminaire colour	silver

OPCJA


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Recessed luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented, die-cast aluminium, powder-coated, rotation angle, swivel angle +/- 25°, silver,

Inclusiv fix connected driver unit, 220-240 V~ / 50-60 Hz, max. 21 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	1.14 0.76	3078.9
2.0 m	2.28 1.53	769.7
3.0 m	3.42 2.29	342.1
4.0 m	4.56 3.05	192.4
5.0 m	5.70 3.82	123.2
	Ø (m)	E0(0°) [lx]

